



FRONTEQ electric powered aerial work platforms feature higher productivity , longer run time and greater uptime .

SPECIFICATION

Self-propelled Scissor Lifts

MODEL	WORKING HEIGHT		WIDTH		TURNING RADIUS*		LIFT CAPACITY		GRADEABILITY**
MEASUREMENT	US	METRIC	US	METRIC	US	METRIC	US	METRIC	
FS0407	21 ft 5 in	6.52 m	2 ft 6 in	0.76 m	5 ft 5 in	1.65 m	617 lb	280 kg	30%
FS0407W	21 ft 5 in	6.52 m	2 ft 8 in	0.81 m	5 ft 5 in	1.65 m	617 lb	280 kg	30%
FS0407E	19 ft 4 in	5.9 m	2 ft 6 in	0.76 m	5 ft 1 in	1.55 m	507 lb	230 kg	25%
FS0507E	22 ft 8 in	6.9 m	2 ft 8 in	0.81 m	5 ft 1 in	1.55 m	507 lb	230 kg	25%
FS0607	25 ft 7 in	7.8 m	2 ft 6 in	0.76 m	5 ft 5 in	1.65 m	507 lb	230 kg	25%
FS0607W	25 ft 7 in	7.8 m	2 ft 8 in	0.81 m	5 ft 5 in	1.65 m	507 lb	230 kg	25%
FS0612	26 ft 7 in	8.1 m	3 ft 10 in	1.18 m	7 ft 7 in	2.3 m	1212 lb	550 kg	30%
FS0812	32 ft 6 in	9.9 m	3 ft 10 in	1.18 m	7 ft 7 in	2.3 m	1014 lb	460 kg	30%
FS1012	38 ft 9 in	11.8 m	3 ft 10 in	1.18 m	7 ft 7 in	2.3 m	705 lb	320 kg	25%
FS1012E	38 ft 9 in	11.8 m	3 ft 10 in	1.18 m	7 ft 7 in	2.3 m	705 lb	320 kg	25%
FS1212	45 ft 3 in	13.8 m	3 ft 10 in	1.18 m	7 ft 7 in	2.3 m	705 lb	320 kg	25%
FS1212E	45 ft 3 in	13.8 m	3 ft 10 in	1.18 m	7 ft 7 in	2.3 m	705 lb	320 kg	25%
FS1414	51 ft 10 in	15.8 m	4 ft 7 in	1.40 m	12 ft 2 in	3.7 m	661 lb	300 kg	25%
FS1414E	51 ft 10 in	15.8 m	4 ft 7 in	1.40 m	12 ft 2 in	3.7 m	661 lb	300 kg	25%
FS0507T	22 ft	6.7 m	2 ft 7 in	0.8 m	2 ft 6 in	0.75 m	441 lb	200 kg	25%

* Outside Radius
 **Gradeability applies to driving on slopes, see operation manual for details regarding slope ratings. Gradeability may vary depending on options installed on equipment.

